

# AGP, MicroAGP & MicroPCI

## MicroAGP



### IBA110-64

MicroAGP daughter card w/ ATI M9 64MB VGA supporting CRT, LVDS, TV-out and 2nd CRT

#### Features:

- Graphics Clock: 250MHz
- Dual Channel LVDS up to 85Mhz per channel
- Supports 18 bit and 24 bit modes for both single and dual channel LVDS
- Max 2D/3D resolution: 2048x1536, 16.7M Colors
- LVDS, TMDS, TV-out: 2048x1536, 1600x1200, 1024x768
- 76mm x 67mm



### IBA110-64A

MicroAGP daughter card w/ ATI M10 64MB AGP8x VGA supporting CRT, LVDS, TV-out and 2nd CRT

#### Features:

- Support for AGP 8X, Microsoft® DirectX® 9.0 programmable shader model 2.0
- Full supported by OpenGL® using custom extensions
- Dual Channel LVDS up to 85Mhz per channel
- Supports 18 bit and 24 bit modes for both single and dual channel LVDS
- Max 2D/3D resolution: 2048x1536, 16.7M Colors
- LVDS, TMDS, TV-out: 2048x1536, 1600x1200, 1024x768
- 76mm x 67mm

## MicroPCI



### IBL59

MicroPCI daughter card w/ Intel® 82559 Ethernet Controller

#### Features:

- Intel® 82559 Single-chip Ethernet controller
- 10 BaseT/100 BaseTX support, full duplex
- PCI V2.1, IEEE802.3, IEEE802.3U compliant
- Backward Compatible with Intel® 82558
- 71mm x 67mm