

AGP, MicroAGP & MicroPCI



IBL39S

MicroPCI daughter card w/ Realtek 8139 Ethernet Controller

Features:

- Realtek 8139 Single-chip Ethernet controller
- 10 BaseT/100 BaseTX support, full duplex
- PCI V2.1, IEEE802.3, IEEE802.3U compliant
- Backward Compatible with traditional LAN facilities
- 71mm x 67mm (with RJ-45 bracket)



IBD99

MicroPCI daughter card w/ Intel® 82559 Ethernet, C&T 69000 2MB VGA

Features

- TFT LCD/DSTN LCD/CRT support
- Resolution / Colors / Refresh Rate
- 1280 x 1024 / 256 / 60Hz
- 1024 x 768 / 16bits (high color) / 85, 75, 60Hz
- 800 x 600 / 24bits (true color) / 85, 75, 60Hz
- Intel® 82559 Single-chip Ethernet controller
- 10 BaseT/100 BaseTX support, full duplex
- PCI V2.1, IEEE802.3, IEEE802.3U compliant
- 71mm x 67mm



IBD63

MicroPCI daughter card w/ SiS 6326 4MB VGA

Features

- Support to 1024x768/ 800x600/ 640x480 in 8/16/24 bit color format @ 120MHz refresh rate
- Support to 1280 x 1024 in 8/16 bit
- Color format @ 85Hz refresh rate
- Display resolution: 320x200 to 1600x1200 pixels
- Multi-Monitor capability; Gamma-corrected video
- 71mm x 67mm