

CMI211-250-956

Expandable Type system for IBASE MI956
Mini-ITX Motherboards

Mini-ITX System



Features

- Mini-ITX system supports IBASE MI956 Mini-ITX motherboards
- Intel® Core™ i7/i5/i3 QC/DC mobile processors
- Supports 3x RS232 & 1x RS232/422/485
- 8x USB2.0 ports/ 2x USB3.0 ports
- Expansion PCI-E(x16) slot
- Supports 1x 2.5" SATA HDD drive bay
- Wall mount kit included

Specifications

System Mainboard	MI956F
CPU Type	Intel® Core™ i7/i5/i3 QC/DC mobile processors
System Speed	2.2GHz
Memory	2x DDR3-1333 SO-DIMM, Max 16GB
Construction	SECC
Chassis Color	Black
Front Panel External I/O	N/A
Rear Panel External I/O	2x COM (Serial Ports) 1x DVI-I, 1 x DVI-D 4x USB2.0 2x USB3.0 1x HDMI 2x RJ45 (Gigabit LAN) 1x Audio Jack (Line out, Line in, Mic in) 1x slot for PCI-E Card 1x AC power-inlet 1x Power On/Off Rock Switch x PWR/HDD LED
Storage	1x 2.5" HDD/SSD bracket
Power Supply	250W ATX power Input Voltage :100 ~ 240V Input Frequency :50 ~ 60Hz
Mounting	Desktop or wall mount (wall mount kit included)
Dimensions	300mm(W) x 225mm(D) x 72mm(H)
Operating Temperature	0°C ~ 45°C (32°F ~ 113°F)
Storage Temperature	-20°C ~ 80°C (-4°F ~ 176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	CFD: 5 grms / 5~500Hz / random operation HDD: 1g / 5~500Hz / random operation

Ordering Information

CMI211-250-956F-L	Chassis for MI956F Mini-ITX, 2.5" 500GB SATA HDD, 8GB DDR3 memory, 250W ATX power supply
CMI211-250-956F-LM	Chassis for MI956F Mini-ITX, without/ CPU/ Memory/HDD, 250W ATX power supply

Dimensions

